



**GOLDEN  
EXTREME**

## **GOLDEN EXTREME GROUP**



Al Fayrouz Building, Shop No. 6,  
Naif, Deira Dubai, U.A.E



info@goldenextreme.com



www.goldenextreme.com



## **STRENGTH FOR EVERY SMALL HAUL**

*Engineered for everyday demands our TBR tyres provide dependable grip, long-lasting durability, and smooth performance for every light commercial journey.*



## ABOUT GOLDEN EXTREME GROUP

Golden Extreme Group, has been shaping the tyre industry since 2006. What began as a focused effort to deliver high-quality tyres across the Middle East and Africa soon evolved into a rapidly growing operation. In 2014, increased market demand fueled further expansion, strengthening our capabilities and industry presence.

From a single vision to a powerful distribution network, Golden Extreme Group today stands as a driving force in the UAE's tyre sector. With 150,000+ sq. ft. of warehouse space, 120+ sales points, and a dedicated team supported by an in-house engineer, we ensure fast access to premium tyre solutions and dependable technical support.

Guided by the values of a family-built legacy, we continue to support fleets, tyre shops, and dealers with reliable products, innovation, and unwavering customer care.

GOLDEN EXTREME GROUP Built on Strength. Driven by Excellence.



## ABOUT FALCON TYRE

In the vast and challenging landscapes of the Middle East and North Africa, where scorching heat meets endless roads, Falcon emerged as a symbol of strength and innovation. Inspired by the UAE's national bird, the brand embodies sharp vision, speed, and resilience qualities that set Falcon apart in a demanding market.

Founded with a mission to engineer tyres built for the region, Falcon focused on creating PCR, TBR, OTR and LTR ranges that could conquer harsh deserts, rugged terrains, and modern city routes with ease. Every Falcon tyre reflects advanced engineering, long-lasting durability, and consistent performance that drivers rely on.

Falcon engineered for the region, trusted on every journey.





# **FALCON TBR TYRES** (TRUCK & BUS RADIAL)

*Built for high mileage, exceptional endurance, and unmatched reliability, Falcon TBR tyres keep your fleet moving with confidence.*

*Engineered specifically for trucks, buses, and heavy commercial vehicles, Falcon TBR tyres offer superior strength, higher load capacity, and long-distance durability. Designed to tackle tough roads and demanding routes, Falcon TBR tyres deliver consistent performance, trip after trip.*

*Falcon TBR - Drive with Confidence.*



# SUPER 617

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
900R20	144/142L	16	15.5	7.00	2800/2650	900/900
1000R20	149/146K	18	15.5	7.50	3250/3000	930/930
1100R20	152/149K	18	16.5	8.00	3550/3250	930/930
1200R20	156/153K	20	17.5	8.50	4000/3650	900/900
1200R24	160/157K	20	16	8.50	4500/4125	900/900
11R22.5	146/143L	16	16	8.25	3000/2725	830/830
12R22.5	152/148M	18	15	9.00	3550/3250	930/930
315/80R22.5	157/154L	20	14.5	9.00	4000/3350	850/850



# SUPER 527

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
11R22.5	144/142M	14	16	8.25	2800/2650	720/720
11R22.5	146/143L	16	16	8.25	3000/2725	830/830
12R22.5	152/149M	18	16.5	9.00	3550/3250	930/930
295/80R22.5	152/149L	18	16	9.00	3550/3250	900/900
315/80R22.5	157/154L	20	15	9.00	4125/3750	900/900
285/75R24.5	144/141M	14	15	8.25	2800/2575	760/760
285/75R24.5	147/144L	16	15	8.25	3075/2800	830/830
295/75R22.5	144/141M	14	15	9.00	2800/2575	760/760
295/75R22.5	146/143L	16	15	9.00	3000/2725	830/830
11R24.5	146/143M	14	15	8.25	3000/2725	720/720
11R24.5	149/146L	16	15	8.25	3250/3000	830/830



# SUPER 517

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
12.00R24	160/157K	20	14.5	8.50	4500/4125	900/900
315/80R22.5	157/154L	20	14.5	9.00	4000/3350	850/850
325/95R24	164/162K	22	14.5	9.00	5000/4725	900/900



# SUPER 668

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
385/65R22.5	160K	20	15	11.75	4500	900



# SUPER 777

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
315/80R22.5	157/154F	20	23	9.00	4125/3750	900/900
12.00R24	160/157K	20	22.5	8.50	4500/4125	900/900



# SUPER 580

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
315/80R22.5	156/150M	20	16	9.00	4000/3350	850/850
12.00R24	160/157K	20	16	8.50	4500/4125	900/900
325/95R24	162/160K	22	16	9.00	5000/4725	900/900



# SUPER 607

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
295/80R22.5	152/149L	18	18	9.00	3550/3150	850/850



# SUPER 608

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
11R22.5	146/143L	16	22	8.25	3000/2725	830/830
12R22.5	152/149M	18	23	9.00	3550/3250	930/930
295/80R22.5	152/149L	18	23	9.00	3550/3250	850/850
315/80R22.5	157/154L	20	18	9.00	4000/3350	850/850



# SUPER 737

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
12R22.5	152/149M	18	22	9.00	3550/3250	930/930
295/80R22.5	152/149L	18	22	9.00	3550/3250	850/850
315/80R22.5	157/154L	20	22	9.00	4000/3350	850/850



# SUPER 619

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
385/65R22.5	160K	20	15	11.75	4500	900



# SUPER 768

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
11R22.5	146/143L	16	22	8.25	3000/2725	830/830
295/80R22.5	152/149L	18	23	9.00	3550/3250	900/900
315/80R22.5	157/154L	20	22	9.00	4000/3350	850/850



# SUPER 613

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
385/65R22.5	160K	20	14.5	11.75	4500	900



# SUPER 903

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
295/80R22.5	152/149F	18	22	9.00	3550/3250	900/900



# SUPER 44

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
7.00R16LT	118/114L	14	11	5.50F	1320/1180	770/770



# SUPER 357

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
11R24.5	149/146M	16	22	8.25	3250/3000	830/830



# SUPER 98

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
12.00R24	160/157K	20	23	8.50	4500/4125	900/900
12.00R24	162/160K	22	23	8.50	4500/4125	900/900



# SUPER 656

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
275/70R22.5	146/143L	16	14	8.25	3000/2725	900/900



# SUPER 329

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
12.00R20	156/153K	20	21	8.50	4000/3650	900/900



# SUPER 769

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
12.00R24	160/157K	20	23	8.50	4500/4125	900/900
325/95R24	164/162K	22	23	9.00	5000/4725	900/900



# SUPER 904

## TBR TYRE

Size	LI/SR	PR	Tread Depth (mm)	Standard Rim	Max Load S/D(kg)	Pressure S/D(kPa)
7.50R16LT	122/118K	14	15.5	6.00G	1500/1320	770/770
8.25R16LT	132/128K	18	15	6.50H	2000/1800	870/870



# SUPER 7

## TBR TYRE

Size	PR	Load index	Speed level	Standard rim	Section width (mm)	Outer diameter (mm)	Design of tread depth (mm)
750R16	16	125/121	L	6.00G	215	805	12.0
825R16	16	128/124	L	6.50H	235	855	13.0
95R17.5	18	143/141	K	6.75	240	842	12.0



# SUPER 8

## TBR TYRE

Size	PR	Load index	Speed level	Standard rim	Section width (mm)	Outer diameter (mm)	Design of tread depth (mm)
650R16	12	110/105	L	5.50F	185	750	10.0
700R16	14	118/114	L	5.50F	200	775	11.0
750R16	16	125/121	L	6.00G	215	805	12.0
825R16	16	128/124	L	6.50H	235	855	12.0
825R20	16	139/137	K	6.5	236	974	14.5



# SUPER 3

## TBR TYRE

Size	PR	Load index	Speed level	Standard rim	Section width (mm)	Outer diameter (mm)	Design of tread depth (mm)
700R16	14	118/114	M	5.50F(TT) / 5/J(TL)	200	775	10.0
85R17.5	16	126/124	M	6.00	215	802	11.0
225/80R17.5	16	129/127	M	6.75	226	805	11.0
265/70R19.5	18	143/141	K	7.50	262	867	14.5
275/80R22.5	18	149/146	M	8.25	276	958	14.5
295/60R22.5	18	150/147	K	9.00	292	926	15.0
295/80R22.5	20	154/151	L	9.00	298	1044	15.0



# SUPER 6

## TBR TYRE

Size	PR	Load index	Speed level	Standard rim	Section width (mm)	Outer diameter (mm)	Design of tread depth (mm)
700R16	14	118/114	L	5.50F	200	775	12.0
750R16	16	125/121	L	6.00G	215	805	13.5
825R16	16	128/124	K	6.50H	235	855	13.5
825R20	16	139/137	J	6.5	236	974	16.0
900R20	16	144/142	J	7.0	259	1019	17.0



# SUPER 88

## TBR TYRE

Size	PR	Load index	Speed level	Standard rim	Section width (mm)	Outer diameter (mm)	Design of tread depth (mm)
325/95R24	22	162/160	K	9.00	325	1228	16.5
1200R24	22	160/156	K	8.5	315	1226	16.5



# SUPER 2

## TBR TYRE

Size	PR	Load index	Speed level	Standard rim	Section width (mm)	Outer diameter (mm)	Design of tread depth (mm)
600R14	10	100/96	L	421	170	680	10.0
600R15	10	101/97	L	4/21	170	705	10.0
700R15	14	117/115	J	5.50F(TT) / 5/J(TL)	200	750	12.0
650R16	12	110/105	M	5.50F(TT) / 5/J(TL)	185	750	10.0
700R16	14	118/114	M	5.50F(TT) / 5/J(TL)	200	775	10.0



# SUPER 1

## TBR TYRE



Size	PR	Load index	Speed level	Standard rim	Section width (mm)	Outer diameter (mm)	Design of tread depth (mm)
215/75R17.5	18	135/133	J	6.00	211	767	11.5
235/75R17.5	18	143/141	J	6.75	233	797	11.5
245/70R17.5	18	134/132	M	7.50	248	789	11.5
245/70R19.5	18	141/140	J	7.50	248	839	14.0





## **OTR** **(Off-The-Road)**

*Falcon OTR tyre are heavy-duty tyres used for construction machines, mining equipment, loaders, dozers, etc., made to handle rough and uneven terrains.*



# FALCON OTR

## OTR TYRE

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
16.00-25	28	28.5	11.25/2.0	430	1495	6700	11500	575	750	TT/TL	H108C E-3 L-3
	32					7300	12500	650	875		
	36					7750	13600	725	975		
15.5-25	12	24.5	12.00/1.3	395	1275	3250	5600	250	400		
	16					3850	6750	325	525		
17.5-25	16	28	14.00/1.5	445	1350	4250	7300	300	475		
	20					5000	8250	400	575		
20.5-25	20	30	17.00/2.0	520	1490	6000	9500	325	450		
	24					6700	10300	400	525		
	28					7500	11500	475	625		
23.5-25	20	33	19.50/2.5	595	1615	7300	10900	300	375		
	24					8000	12500	350	475		
	28					8750	13600	400	550		
26.5-25	28	35	22.00/3.0	675	1750	10000	15500	350	475		
	32					11200	17000	425	550		
29.5-25	28	38	25.00/3.5	750	1875	11500	17500	325	425		
	34					12500	19000	375	500		

